

## DATA SHEET

Code: PFH610V-IR-V2

## OUTDOOR SIDE OPENING HOUSING **PFH610V-IR-V2** DAHUA

Half-open housings allow to easy access to inside mounted elements in contrast to sliding housings. Attention: The camera ground shouldn't be connected to the housing ground.

Built-in Infra-Red illuminator enables night monitoring. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).



External dimensions:	404 x 164 x 132 mm
Internal dimensions:	215 x 90 x 83 mm
Glass dimensions:	Ø 60 mm
Material:	Aluminum - powder painted + PC
Thermostat:	<b>&gt;</b>
IR illuminator:	100 m
Power supply:	24 V AC / 5 A (max)
Power consumption:	≤ 55 W
"Index of Protection":	IP66
Vandal-proof:	IK10
Main features:	<ul> <li>The product is adapted to work outdoors (heater and fan cooler built-in)</li> <li>Controlling the IR illuminator via RS-485</li> <li>Bracket not included in the kit</li> </ul>
Operation temp:	-40 °C 60 °C
Weight:	2.52 kg
Manufacturer / Brand:	DAHUA
Guarantee:	3 years