

Code: IPC-G26E-IMOU

IP CAMERA **IPC-G26E-IMOU** Wi-Fi, BULLET - 1080p 2.8 mm

The cameras of the IMOU series have been designed with special care to simplify the configuration and operation. In combination with the user friendly IMOU platform, the IMOU series devices allow anyone to create a simple and effective surveillance system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 50 m.

The device is ideal for eg. as a baby monitor, with mobile image view on smartphone and possibility of bi-directional audio transmission.

Attention! The IMOU series devices do not have a WEB interface. In order to obtain optimal performance of IMOU series cameras, it is recommended to use DAHUA Micro SD memory cards.



Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm
View angle:	115 °
White light LED illuminator range:	30 m
S/N ratio:	> 50 dB
Image compression method:	H.265 / H.264
Audio:	• Microphone built-in, • Speakers built-in, • Bi-directional audio streaming support, • Alarm siren - 110 dB
Main stream frame rate:	25 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45), Wi-Fi IEEE 802.11 b/g/n

Network protocols:	TCP, DHCP
WEB Server:	—
ONVIF:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	• Wi-Fi module - IEEE 802.11 b/g/n, Range : 100 m (open area) • Motion Detection, • D-ZOOM - Digital Zoom, • RESET button, • PIR detector - Built-in
Power supply:	12 V DC / 540 mA
Power consumption:	≤ 6.5 W
Mobile phones support:	Access by a cloud (P2P) • Android: Free application IMOU • iOS (iPhone): Free application IMOU
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
"Index of Protection":	IP67
Operation temp:	-30 °C ... 50 °C
Weight:	0.42 kg
Dimensions:	166 x 79 x 79 mm
Supported languages:	—
Manufacturer / Brand:	DAHUA / IMOU
Guarantee:	2 years