

Code: ARCHER-MR600

ACCESS POINT 4G+ LTE Cat. 6 +ROUTER **ARCHER-MR600** Wi-Fi 2.4 GHz, 5 GHz 867 Mbps + 300 Mbps TP-LINK

The ARCHER-MR600 Wireless Router, operating in accordance with the IEEE 802.11 b/g/n/ac standard, allows to share a network connection between several users in areas that are covered by 3G/4G signal.

The device does not require any additional configuration, it is ready to use immediately after placing the SIM card inside and connecting the power supply.



Frequency range:	2.4 GHz , 5 GHz
Antenna type:	WiFi - built-in , 2 x 4G LTE
Standards:	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n, • IEEE 802.11 a/n/ac
Baud rates:	<ul style="list-style-type: none"> • 5 GHz : 867 Mbps (max) + 2.4 GHz : 300 Mbps (max) • LTE : 300 Mbps
LAN ports:	<ul style="list-style-type: none"> • 1 x 10/100/1000 Mbps - LAN/WAN • 3 x 10/100/1000 Mbps - LAN
Receiver sensitivity:	5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -66 dBm • 11ac HT40: -63 dBm • 11ac HT80 : -59 dBm • 11n HT20: -73dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -74dBm • 11n HT20: -72 dBm • 11n HT40: -69 dBm
LTE:	✓



DATA SHEET

QSS:	—
WDS:	✓
Transmitter power:	max. 23 dBm
Main features:	<ul style="list-style-type: none">• IP-layer bandwidth control mechanism• Local, remote or via TP-Link Cloud management• Support for TP-Link OneMesh™ technology• SIM socket• WPS/RESET button
Power supply:	12 V DC / 1.5 A (power adapter included)
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	95 % (non-condensing)
Weight:	0.478 kg
Dimensions:	230 x 163 x 37 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years