

Code: ASA1222G

TIME & ATTENDANCE RECORDER **ASA1222G** DAHUA

Time Attendance Recorder has a memory to store up to 1000 users + 5 administrators and up to 2000 different fingerprints (max 3 for one user). The device enables storing up to 100 000 events, taking into account the programmable work schedule (individual and group) and the distinction of: standard events, overtime, lateness and earlier exits.

The identification of each user can be done using the PIN code consisting of 1 ... 8 digits, a fingerprint or with using the proximity reader working in 13.56 MHz S50 standard. It is also possible to create a user with only one identification method.

The device can work both autonomously and as part of a system based on SmartPSS software.



| | |
|--------------------------------|--|
| FINGERPRINT READER: | |
| Identification time: | < 1.5 s |
| FAR (False Acceptance Rate): | ≤ 0.00004 % |
| FRR (False Rejection Rate): | ≤ 0.15 % |
| PROXIMITY READER: | |
| Cards support: | 13.56 MHz S50 |
| Reading distance of prox-keys: | 1 ... 3 cm |
| Keyboard built-in: | ✓ |
| Autonomous operation: | ✓ |
| Doorbell button: | — |
| Communication: | <ul style="list-style-type: none"> • TCP/IP, • USB - The ability to firmware upgrade |
| Relay output: | 1 x NO/NC |
| Internal memory: | 8 MB |
| Memory card slot: | — |
| Number of supported readers: | — |
| Default admin user / password: | admin / admin |

| | |
|--------------------------------|---|
| Main features: | <ul style="list-style-type: none"> • Full support via network • Possibility of integration with systems based on SmartPSS software, • 1000 indexed users, • 2000 indexed fingerprints (maximum 3 per user), • Possibility to program up to 1000 user cards, • Non-volatile log buffer of the last 100 000 events, • LCD display - 2.4 " • Sound signaling • Software update via network • It is possible to connect the door release button • The possibility of programming group or individual work schedules, taking into account the permissible time of lateness and earlier exit • The distinction of standard events, overtime, lateness and earlier exits • Data export to USB flash memory in "*.xls" format • The device can signal when the shift ends with an audible signal • built-in battery - 2600 mAh |
| Power supply: | 12 V DC / 1000 mA (power adapter included) |
| Weight: | 0.41 kg |
| Dimensions: | 181 x 136 x 32 mm |
| Operation temp: | 0 °C ... 55 °C |
| Permissible relative humidity: | 10 % ... 90 % |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |