

Code: IP-9-11-L2

SWITCH POE **IP-9-11-L2** 8-PORT ATTE

The IP-9-11-L2 set consists of 2 XPOE-6-11-OF modules and the APS-90-480-OF switching power supply enclosed in the ABOX-L2 external enclosure with IP56 tightness class.

The LONG RANGE operation mode allows to increase the range of power and data transmission for ports LAN 1 ... LAN 4 to 280m while limiting the network bandwidth for these ports to 10Mbps. It is possible to use the LONG RANGE mode independently in each of the XPOE-6-11-OF modules.



LAN ports:	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE
Management:	—
LED diodes:	Power, LAN
Transmission speed:	10 / 100 Mbps : 1 Port LAN + 9 LAN & PoE ports
Maximal output power:	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports
Maximal total power:	96 W
Operation modes:	<ul style="list-style-type: none"> • Normal : 100 m @ 10/100 Mb/s - 1 ... 5 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - Port 5





DATA SHEET

Main features:	<ul style="list-style-type: none">• Possible cascading device connection (power transmission between devices using Passive PoE via LAN 5 port)• The LAN 5 (PoE IN/OUT) port can be used to power PoE devices as well as to draw power from other devices• The output PoE voltage is equal to the input voltage• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports• The modular design streamlines service tasks and enables quick and easy system expansion• The raster system of module assembly facilitates the expansion of the device by further modules• The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement
Power supply:	230 V AC - cable terminals
Weight:	1.05 kg
Dimensions:	248 x 222 x 96 mm
Manufacturer / Brand:	ATTE
Guarantee:	3 years