

Code: ATE-CAM-IPC735

IP MOBILE CAMERA **ATE-CAM-IPC735** - 1080p 2.8 mm AUTONE

Mobile IP camera equipped with M12, 6-pin - code A connector, providing image in maximum resolution Full HD, 1080p.



Standard:	TCP/IP
Sensor:	1/2.7 " SC2235 CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"> • 95 ° (manufacturer data) • 90 ° (our tests result)
Range of IR illumination:	10 m
S/N ratio:	≥ 58 dB
RS-485 interface:	—
Memory card slot:	—
Image compression method:	H.264
ONVIF:	✓
Alarm inputs / outputs:	—



DATA SHEET

Audio:	—
Main stream frame rate:	20 fps @ 1080p
Network interface:	10/100 Base-T - M12, 6-pin socket - Code A
Main features:	<ul style="list-style-type: none">• Motion Detection• Auto White Balance• AGC - Automatic Gain Control• BLC - Back Light Compensation
Power supply:	12 V DC / 600 mA
Power consumption:	≤ 5 W
Mobile phones support:	—
Default IP address:	192.168.1.2
Default user password:	admin / -
Web browser access ports:	8899
PC client access ports:	8899
Housing:	Dome, Metal
Color:	Black
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.27 kg
Dimensions:	90 x 77 x 65 mm
Supported languages:	English
Manufacturer / Brand:	AUTONE
Guarantee:	2 years

