

Code: OMEGA-PTZ-22H4-4

AHD, HD-CVI, HD-TVI, CVBS SPEED DOME CAMERA OUTDOOR **OMEGA-PTZ-22H4-4** - 1080p 2.8 ... 12 mm

Small dimensions, outdoor PTZ camera with motozoom lens.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. During transmission there are no delays and is maintained the original, high quality image.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). Camera is according to IP66 Index of Protection norm.

Attention!

In order to change the standard via RS-485 (using the keyboard or from the recorder level):

- 2x call the preset 137 to change to AHD.
- 2x call the preset 138 to change to TVI.
- 2x call the preset 139 to change to CVI.
- 2x call the preset 140 to change to CVBS.



Standard:	AHD, HD-CVI, HD-TVI, CVBS
Sensor:	1/2.9 " Sony CMOS
Matrix size:	2.1 Mpx
Resolution:	• AHD, HD-CVI, HD-TVI : 1920 x 1080 px - 1080p • CVBS : 960 x 576 px - 960H
Range of IR illumination:	45 m
Lens:	2.8 ... 12 mm - Motozoom
View angle:	• 91 ° ... 28 ° (manufacturer data) • 76 ° ... 30 ° (our tests result)
Optical zoom:	x 4
Digital zoom:	x 16
Rotation speed depending on ZOOM level:	—
Auto IR illuminator:	✓
Horizontal rotation range:	0 ° ... 355 ° - Rotation of the head is limited by stops

Vertical rotation range:	0 ° ... 70 °
Rotation speed (manual control):	25 °/s (horizontal) , 20 °/s (vertical)
Preset rotation speed:	25 °/s (horizontal) 20 °/s (vertical)
PTZ control:	Via interface RS-485, Default address : 1, 2400 bps
Protocols:	Pelco-D, Pelco-P (auto detection)
S/N ratio:	> 50 dB
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp 75 Ω
Audio:	—
Number of presets:	220
Route settings:	8
Horizontal scan:	—
Park action:	Calling the preset position after a specified dwell time
Alarm inputs / outputs:	—
Main features:	• ICR - Movable InfraRed filter • 3D-DNR - Digital Noise Reduction • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines
OSD menu:	✓
Power supply:	12 V DC / 940 mA
Power consumption:	≤ 11.3 W
Housing:	Speed Dome, Plastic
Color:	White
"Index of Protection":	IP66
Vandal-proof:	—
Operation temp:	-40 °C ... 60 °C
Weight:	0.57 kg
Dimensions:	Ø 111 x 102 mm
Supported languages:	English
Guarantee:	2 years