

Code: AXD-200/IT

MULTIPURPOSE WIRELESS DETECTOR **AXD-200/IT** ABAX/ABAX2 SATEL

The AXD-200/IT wireless detector can work in one of the 7 modes, which makes it an extremely universal device. Depending on your needs, the device can be configured as: two-channel magnetic detector, magnetic detector with roller shutter (for wired sensor), shock detector with reed switch, position sensor, temperature detector or water flood detector (FPX-1 external probe required - available separately).

The AXD-200/IT supports the other devices compatible with wireless ABAX/ABAX2 system.



Support:	ABAX/ABAX2
Alarm signaling:	Signal to control panel
Frequency band:	868 MHz ... 868.6 MHz
Radio communication range (at open area):	• ≤ 500 m @ ABAX, • ≤ 2000 m @ ABAX2
Battery:	CR123A 3 V - 3.0 V (included)
Backup time:	~ 2 years
Protection class (Grade):	2

Main features:	• Operation modes : - Magnetic detector - Dual channel magnetic detector - Magnetic detector with roller shutter input - Input to an additional wired detector - Shock and magnetic detector - Detection of shocks and vibrations associated with attempts to force a door or window - Reorientation detector - Detecting a change in position of an object - Temperature Sensor - Temperature measurement in the range: -10°C ... +55°C, Two programmable temperature thresholds (upper and lower) - Water flood detector - The required FPX-1 probe is available separately • Tamper detection - opening the enclosure, removing from mounting surface • Remote configuration • Remote update of module software • The LED to indicate violations in test mode, easy start-up and later maintenance of the system
Operation temp:	-10 °C ... 55 °C
Color:	White
Weight:	0.023 kg
Dimensions:	20 x 102 x 23 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years