

Code: VT03211D-P2-S1

VIDEO DOORPHONE **VT03211D-P2-S1** DAHUA

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.

ATTENTION! The device does not support the Dahua analogue system.



Compatibility:	DAHUA
Sensor:	1/2.8", 2 Mpx CMOS
View angle:	134 °
Image compression method:	H.264
IR illuminator:	✓
proximity reader built-in:	Access control cards - Mifare S50
The number of subscribers served:	2
UTP category:	UTP cat. 5e
Main features:	<ul style="list-style-type: none"> • It can only work with the mobile application, without the VTH monitor • The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - opening the enclosure, • Vandal-proof front panel, • Output for the additional lock release button

Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS There are also other versions of mobile applications: gDMSS Plus, iDMSS Plus
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 500 mA
Power consumption:	≤ 6 W
Housing:	Zinc alloy, Waterproof
Color:	Graphite
"Index of Protection":	IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone
Mechanical strength:	IK08
Operation temp:	-30 °C ... 60 °C
Weight:	0.46 kg
Dimensions:	182 x 101 x 31 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years