

Code: VTO3211D-P-S1

## VIDEO DOORPHONE **VTO3211D-P-S1** DAHUA

The device works with video doorphones, and other DAHUA panels. Video Doorphone is mounted in a surface housing.

ATTENTION! The device does not support the Dahua analogue system.



|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compatibility:                    | DAHUA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Sensor:                           | 1/2.8 ", 2 Mpx CMOS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| View angle:                       | 134 °                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Image compression method:         | H.264                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| IR illuminator:                   | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| proximity reader built-in:        | Access control cards - 13.56 MHz S50                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| The number of subscribers served: | 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| UTP category:                     | UTP cat. 5e                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Main features:                    | <ul style="list-style-type: none"> <li>• It can only work with the mobile application, without the VTH monitor</li> <li>• The function of the monitor with the ability to open the door can be a smartphone, tablet or the VTH indoor panel</li> <li>• Bidirectional communication,</li> <li>• Microphone built-in,</li> <li>• Speakers built-in,</li> <li>• Tamper detection - opening the enclosure,</li> <li>• Vandal-proof front panel,</li> <li>• Output for the additional lock release button</li> </ul> |

|                        |                                                                                                                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">DMSS</a></li><li>• iOS (iPhone): Free application <a href="#">DMSS</a></li></ul> |
| Power supply:          | <ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 500 mA</li></ul>                                                                                                               |
| Power consumption:     | ≤ 6 W                                                                                                                                                                                                     |
| Housing:               | Zinc alloy, Waterproof                                                                                                                                                                                    |
| Color:                 | Graphite                                                                                                                                                                                                  |
| "Index of Protection": | IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone                                                                                                      |
| Mechanical strength:   | IK08                                                                                                                                                                                                      |
| Operation temp:        | -30 °C ... 60 °C                                                                                                                                                                                          |
| Weight:                | 0.46 kg                                                                                                                                                                                                   |
| Dimensions:            | 182 x 101 x 31 mm                                                                                                                                                                                         |
| Supported languages:   | Polish, English, Bulgarian, Czech, Finnish, Slovenian, Slovak, Hungarian                                                                                                                                  |
| Manufacturer / Brand:  | DAHUA                                                                                                                                                                                                     |
| Guarantee:             | <b>3 years</b>                                                                                                                                                                                            |