

Code: DS-KV6113-WPE1

WIRELESS VIDEO DOORPHONE **DS-KV6113-WPE1** Wi-Fi / IP Hikvision

Wi-Fi / IP video doorphone is dedicated to work with II generation IP Hikvision internal panels.

Video Doorphone is mounted in a surface housing.



Sensor:	2 Mpx
Resolution:	1920 x 1080
Camera view angle:	129 °
IR illuminator:	✓
LED illuminator:	—
PIR detector:	—
Doorbell button:	1 pcs
proximity reader built-in:	13.56 MHz S50
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface:	<ul style="list-style-type: none"> • Ethernet • Wi-Fi
RS-485 interface:	✓
Video output:	—



DATA SHEET

Video format:	H.264
Supported audio formats:	G.711
Alarm inputs:	4 pcs
Main features:	<ul style="list-style-type: none">• Bidirectional communication,• Full support via network : WiFi / LAN,• Tamper detection - removing from mounting surface,• Video Doorphone is mounted in a surface housing• The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel
Power supply:	<ul style="list-style-type: none">• PoE (802.3af)• 12 V DC / 830 mA (max)
Power consumption:	< 10 W (operation)
Housing:	Plastic
Mount:	Surface
Color:	Black + Gray
"Index of Protection":	IP65
Operation temp:	-40 °C ... 53 °C
Weight:	0.26 kg
Dimensions:	65 x 139 x 30 mm
Supported languages:	Polish, English, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305301760
Guarantee:	3 years