

Code: DS-KIS702

## VIDEO DOORPHONE KIT **DS-KIS702** Hikvision

Two-wire HIKVISION video doorphone system with 7" touch monitor and controller equipped with 4 2-wire buses. Video Doorphone is mounted in a surface housing.

The device has the ability to work with the [Hik-Connect](#) application for mobile devices.

The attached DS-KAD704 controller also enables the connection of the video doorphone system to the LAN network and via it to the Internet.



Compatibility:	HIKVISION 2-wire
Doorbell button:	1 pcs
Sensor:	2.1 Mpx CMOS
Camera resolution:	1920 x 1080 - 1080p
Camera view angle:	180 °
Image compression method:	H.264
IR illuminator:	✓
Network protocols:	TCP/IP, RTSP
Alarm inputs:	4 pcs
Relay outputs:	2 x NO/NC
Main features:	<ul style="list-style-type: none"> <li>• Bidirectional communication,</li> <li>• Microphone built-in,</li> <li>• Speakers built-in,</li> <li>• Noise suppression and echo cancellation,</li> <li>• Tamper detection - removing from mounting surface ,</li> </ul>
Power supply:	<ul style="list-style-type: none"> <li>• 24 V DC - HIKVISION 2-wire</li> <li>• 12 V DC (power adapter not included)</li> </ul>
Power consumption:	<ul style="list-style-type: none"> <li>&lt; 16 W @ 24 V DC</li> <li>&lt; 20 W @ 12 V DC</li> </ul>
Operation temp:	-40 °C ... 60 °C

Housing:	Metal
Color:	Black
"Index of Protection":	IP65
Weight:	0.38 kg
Dimensions:	100 x 98 x 44 mm

## INDOOR PANEL:

Compatibility:	Hikvision 2-wire modular video doorphones
Shield:	7 " - capacitive touch screen
Resolution:	1024 x 600
Internal memory:	128 MB (built-in)
Main features:	<ul style="list-style-type: none"> <li>• Wi-Fi Module - IEEE 802.11 b/g/n,</li> <li>• Microphone built-in,</li> <li>• Speakers built-in,</li> <li>• Bidirectional communication,</li> <li>• Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,</li> <li>• Automatically capture and save photos if there is no response to the bell button,</li> <li>• IP Hikvision cameras support,</li> <li>• The ability of direct communication between two or more panels,</li> <li>• Register a short voice message if there is no response to the bell button</li> <li>• Support for capturing a photo during video calls</li> <li>• The microSD - max. 32 GB cards support - 16 GB included,</li> <li>• The device is fully configurable via the <b>iVMS4200</b> software.</li> <li>• In addition, the device has the ability to work with the <b>Hik-Connect</b> application on mobile devices</li> </ul>
Controlling:	capacitive touch screen
Default administrator password:	888999
Default password for securing the zone:	123456
Alarm inputs:	8
Alarm outputs:	2
Power supply:	24 V DC - HIKVISION 2-wire
Power consumption:	≤ 6 W
Color:	Black + Silver
Operation temp:	-10 °C ... 50 °C
Weight:	0.33 kg
Dimensions:	200 x 140 x 25 mm

## ENCLOSURE:

Number of mounted modules:	1 pcs
Material:	Aluminum
Color:	Graphite
Weight:	0.32 kg

External dimensions:	117 x 107 x 37 mm
----------------------	-------------------

Switch:

Number of ports:	4 x HIKVISION 2-wire , 1 x RJ-45
Compatibility:	2-wire doorphone installation Hikvision
Main features:	DIN, TS-35 rail mounting
Power supply:	24 V DC
Housing:	Plastic
Operation temp:	-10 °C ... 50 °C
Weight:	0.25 kg
Dimensions:	144 x 90 x 66 mm

General information:

Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305301917
Guarantee:	<b>3 years</b>

