DATA SHEET

Code: VMT-101M-S

MONITOR 1xVIDEO, VGA, HDMI, AUDIO **VMT-101M-S** 10.1 " VILUX



CCTV monitor with solid metal housing.

This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems. Monitor is equipped with speakers mounted on the bottom side of the housing.

The device is designed to continuous work in closed spaces.

Screen size:	10.1 "
Native resolution:	1280 x 800 px
Aspect ratios:	16 : 10
Matrix type:	TFT-LCD color matrix
Matrix backlight:	In LED technology
Supported standards:	PAL/NTSC
Contrast:	800 : 1
Brightness:	300 cd/m^2
Viewable angles:	• 160 ° - horizontal • 160 ° - vertical
Response time:	8 ms
Speakers built-in:	2 x 1 W

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Signal connectors:	• Composite Video (BNC) sockets: 1x in, 1x out, • 1x HDMI, • 1x VGA, • 1x Audio (Jack 3.5mm socket)
Housing type:	Metal
Monitor mounting standard:	VESA 75
Power supply:	12 V DC / 4 A (power adapter included)
Power consumption:	< 12 W
Monitor control:	OSD - by monitor control keys
Operation temp:	0 °C ... 40 °C
Weight:	1.49 kg
Dimensions:	• 239 x 205 x 84 mm (with stand) • 239 x 170 x 43 mm (without stand)
Supported languages:	English, Spanish, French, German, Italian
Manufacturer / Brand:	VILUX
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60