

DATA SHEET

Code: TL-EC230-G1 ROUTER **TL-EC230-G1** 2.4 GHz, 5 GHz 450 Mbps + 867 Mbps TP-LINK

With 867 Mbps wireless speeds over the crystal clear 5 GHz band and 450 Mbps over the 2.4 GHz band, TL-EC230-G1 offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band – all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.

The MU-MIMO technology supports up to 2 devices simultaneously, increasing Wi-Fi bandwidth. Beamforming technology detects the location of connected devices and focuses Wi-Fi towards them to create stronger connections.



Frequency range:	2.4 GHz, 5 GHz
Antenna type:	4 x Omnidirectional antenna - Integrated
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Baud rates:	450 Mbps + 867 Mbps
LAN ports:	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink
LED indicators:	Power, 2.4 GHz WLAN, 5 GHz WLAN, Ethernet, WAN, WPS
DDNS:	*
DHCP server:	¥
Firmware update:	¥
Protections:	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface:	Web browser



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Power supply:	12 V DC / 1 A (power adapter included)
Main features:	 TP-Link OneMesh[™] support Beamforming technology detects the location of connected devices and focuses Wi- Fi towards them to create stronger connections Firewall Internet access filtering Static / dynamic routing Built-in 4-port switch Wireless transmission statistics The WPS function allows to easy establish an encrypted connection QoS WMM (Wi-Fi Multimedia) Rate limit Access control Remote management DMZ parental control Guest Network - a separate and secure network for guests
Operation temp:	0 °C 40 °C
Permissible relative humidity:	5 % 90 % (non-condensing)
Weight:	0.36 kg
Dimensions:	257 x 161 x 215 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

