

Code: BCS-DMIP1501IR-E-V

## IP CAMERA **BCS-DMIP1501IR-E-V** - 5 Mpx 2.8 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

Camera is according to IP67 Index of Protection norm.



|                           |  |
|---------------------------|--|
| Standard:                 | TCP/IP   |
| Sensor:                   | 1/2.3 " Progressive Scan CMOS  |
| Matrix size:              | 5 Mpx  |
| Resolution:               | 2592 x 1944 - 5 Mpx ,<br>2688 x 1520 - 4 Mpx ,<br>2048 x 1536 - 3.7 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p<br>1280 x 960 - 1.3 Mpx<br>1280 x 720 - 720p |
| Lens:                     | 2.8 mm   |
| View angle:               | <ul style="list-style-type: none"> <li>• 103 ° (manufacturer data)</li> <li>• 95 ° (our tests result)</li> </ul>   |
| Range of IR illumination: | 30 m   |
| RS-485 interface:         | —  |
| Memory card slot:         | Micro SD memory cards up to 256GB support (possible local recording)   |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG  |



# DATA SHEET

|                                |  |
|--------------------------------|--|
| Alarm inputs / outputs:        | —  |
| Audio:                         | <ul style="list-style-type: none"><li>• Microphone built-in</li><li>• Audio detection</li></ul>  |
| Main stream frame rate:        | 20 fps @ 5 Mpx<br>25 fps @ 4 Mpx   |
| Network interface:             | 10/100 Base-T (RJ-45)  |
| Network protocols:             | IPv4/IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, IEEE 802.1x, Bonjour  |
| WEB Server:                    | Built-in   |
| Max. number of on-line users:  | 20   |
| ONVIF:                         | 18.12  |
| Main features:                 | <ul style="list-style-type: none"><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>• ICR - Movable InfraRed filter</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Motion Detection</li><li>• Configurable Privacy Zones</li><li>• Mirror - Mirror image</li><li>• IVS analysis : intrusion, crossing the line (tripwire)</li></ul> |
| Mobile phones support:         | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">DMSS</a></li><li>• iOS (iPhone): Free application <a href="#">DMSS</a></li></ul>  |
| Default IP address:            | 192.168.1.108  |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start   |
| Web browser access ports:      | 80, 37777  |
| PC client access ports:        | 37777  |
| Mobile client access ports:    | 37777  |
| Port ONVIF:                    | 80   |
| RTSP URL:                      | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream  |
| Power supply:                  | <ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 600 mA</li></ul>  |
| Power consumption:             | < 7.2 W  |
| Housing:                       | Dome - Metal   |
| Color:                         | White  |
| "Index of Protection":         | IP67   |
| Operation temp:                | -40 °C ... 60 °C   |
| Weight:                        | 0.53 kg  |



# DATA SHEET

---

|                       |                 |
|-----------------------|-----------------|
| Dimensions:           | Ø 106 x 94 mm   |
| Supported languages:  | Polish, English |
| Manufacturer / Brand: | BCS             |
| Guarantee:            | <b>3 years</b>  |