

Code: ASI8223Y-A-V3

## ACCESS CONTROLLER **ASI8223Y-A-V3** - 1080p DAHUA

Access controller with face recognition function.



Sensor:	CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p

General information:

Standard:	TCP/IP
Range of IR illumination:	5 m
White light LED illuminator range:	5 m
Temperature measurement:	—
Face recognition distance:	0.3 m ... 2.0 m (max 100 000 faces in the database)
RFID proximity reader built-in:	13.56 MHz S50
Internal memory:	Support storage of 100 000 records
Video output:	—
RS-485 interface:	✓



# DATA SHEET

RS-232 interface:	✓
Wiegand interface:	✓
USB:	1 x USB 2.0
Memory card slot:	—
Alarm inputs / outputs:	1 / 1
Audio:	Speaker built-in
Network interface:	1 x 10/100 Base-T (RJ-45)
Network protocols:	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server:	Built-in
ONVIF:	—
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Main features:	<ul style="list-style-type: none"><li>• Built-in LCD display showing the image from the video camera - 10.1 " capacitive touch screen, 1280 x 800 px</li><li>• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above</li><li>• Wiegand 34/26</li><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• LED indication</li><li>• Buzzer for acoustic signaling of some system events</li><li>• AGC - Automatic Gain Control</li><li>• Sharpness - sharper image outlines</li><li>• Day/Night mode (color/b&amp;w/auto)</li><li>• RESET button</li></ul>
Power supply:	12 V DC / 2 A (power adapter included)
Power consumption:	≤ 24 W
Housing:	Aluminum + Tempered glass
Color:	Black + Silver
"Index of Protection":	IP65 ( after additional sealing the housing connection with the mounting surface, e.g. with silicone )
Operation temp:	-30 °C ... 60 °C
Weight:	5.51 kg
Dimensions:	465 x 191 x 121 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>