

Code: TL-SF1008LP

## SWITCH POE **TL-SF1008LP** 8-PORT TP-LINK

Due to reliability and ensuring high quality of transmission, the TL-SF1008LP 10/100M 8-port PoE desktop type switch is perfect solution for expanding home or office network. Four ports support Power over Ethernet (PoE) function.

Switch has the priority function which will help protect the system when the system power is overloaded. The power consumption of the devices powered by PoE is up to 41W. The devices connected to the ports with higher priority are powered in the first place.

**Attention!** Order of priority: port-1 > port-2 > port-3 > port-4. This feature protects the system in case of overloading.



|                       |  |
|-----------------------|--|
| LAN ports:            | 8 x RJ45 ( 4 PoE )   |
| Management:           | —  |
| LED diodes:           | Power, Link/Act, PoE, PoE Max  |
| Transmission speed:   | 10 / 100 Mbps : 4 Port LAN + 4 LAN & PoE ports   |
| Maximal output power: | 15.4 W / port PoE  |
| Maximal total power:  | 41 W   |
| MAC addresses table:  | 2k   |
| Operation modes:      | <ul style="list-style-type: none"> <li>• Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 - 1 ... 4 ports</li> <li>• Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6</li> </ul>   |
| Main features:        | <ul style="list-style-type: none"> <li>• High priority ports : 1 ... 2 ports - Dedicated to video transmission</li> <li>• Support of the 3 network modes: Priority, Standard, Extend</li> <li>• (RJ45) 10/100 Mb Auto-Negotiation, Auto MDI/MDIX</li> <li>• Auto-learning and Auto-aging functions support for MAC addresses</li> <li>• IEEE802.3x Flow Control</li> </ul> |
| Certificates:         | FCC, CE, RoHS  |
| Power supply:         | 53.5 V DC / 0.81 A (power adapter included)  |
| Weight:               | 0.34 kg  |
| Dimensions:           | 171 x 100 x 28 mm  |
| Manufacturer / Brand: | TP-LINK  |
| Guarantee:            | <b>3 years</b>   |