

Code: UT-620A

LOW RESISTANCE METER **UT-620A** UNI-T

The UT-620A meter allows you to measure low resistances (even a few mΩ). Due to the intended use of the device, the measurement should always be performed with the use of dedicated measurement probes attached to the product.



| | |
|---------------------------------------|--|
| Resistance measurement: | 120 mΩ ± (0.25% + 25) @ 0.01 mΩ , 600 mΩ ± (0.25% + 25) @ 0.01 mΩ , 6 Ω ± (0.25% + 25) @ 0.0001 Ω , 60 Ω ± (0.25% + 25) @ 0.001 Ω , 600 Ω ± (0.25% + 25) @ 0.01 Ω , 6 kΩ ± (0.75% + 30) @ 0.0001 kΩ |
| Automatic change of measuring ranges: | — |
| RS-232: | — |
| USB: | ✓ |
| Main features: | <ul style="list-style-type: none"> • Hold - stopping the meter reading, • 4-lead measurement, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case |
| Power supply: | Built-in 7.4V / 4000mAh battery, 9V / 4A power adapter included |
| Weight: | 1.33 kg |
| Dimensions: | 269 x 182 x 60 mm |
| Manufacturer / Brand: | UNI-T |



DATA SHEET

| | |
|------------|---------|
| Guarantee: | 2 years |
|------------|---------|