

Code: XPOE-6-11-S2

SWITCH POE **XPOE-6-11-S2** 5-PORT ATTE

The XPOE-6-11-S2 switch is designed to supply IP cameras operating in the IEEE 802.3af/at standard. 5 ports support Power over Ethernet (PoE) function.

The LONG RANGE operation mode allows to increase the range of power and data transmission for ports LAN 1 ... LAN 4 to 280m while limiting the network bandwidth for these ports to 10Mbps.



LAN ports:	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T, PoE 802.3af/at / Passive PoE
Management:	—
LED diodes:	Power, LAN
Transmission speed:	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
Maximal output power:	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 4 ports, • 70 W @ Passive PoE - Port 5, • 30 W @ PoE (802.3af/at) - 1 ... 5 ports
Maximal total power:	50 W
Operation modes:	<ul style="list-style-type: none"> • Standard : 100 m @ 10/100 Mb/s - 1 ... 6 ports • Long Range : 280 m @ 10 Mb/s - 1 ... 4 ports ; 100 m @ 10/100 Mb/s - 5, 6 ports



DATA SHEET

Main features:	<ul style="list-style-type: none">• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports• Wide input voltage range• Up to 70W power on the LAN_5 PoE IN/OUT port• Powered by a screw connector (V_{in}) or from another switch PoE PASSIVE (PoE IN/OUT port)• Cascade powering possible - one switch supplies another one - PoE IN/OUT port• Output voltage for PoE devices $V_{out} = V_{in}$• "Index of Protection" : IP56• There are cable glands in the housing : 6 x M16
Power supply:	10 ... 56 V DC
Operation temp:	-25 °C ... 50 °C
Weight:	0.34 kg
Dimensions:	158 x 118 x 77 mm
Manufacturer / Brand:	ATTE
Guarantee:	2 years