DATA SHEET

Code: IP-8-20-L2

SWITCH POE **IP-8-20-L2** 8-PORT ATTE

The IP-8-20-L2 set consists of the XPOE-10-20-OF switch module and the APS-90-480-OF switching power supply enclosed in the ABOX-L2 external enclosure with IP56 tightness class.



LAN ports:	• 2 x RJ45 10/100/1000 Base-TX - Uplink, • 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE
Management:	–
LED diodes:	Power, LAN
Transmission speed:	• 10 / 100 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 LAN ports
Maximal output power:	• 40 W @ Passive PoE - 1 ... 8 ports, • 30 W @ PoE (802.3at) - 1 ... 8 ports, • 15.4 W @ PoE (802.3af) - 1 ... 8 ports
Maximal total power:	96 W

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Main features:	• Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade @ 90 W • Built-in switching power supply : 48 V DC / 96 W • Efficiency : 92 % • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • Electronic fuse independently for each PoE channel • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • The ABOX-L2 mounting enclosure is equipped with 11 cable entries with glands in the 10 x M16 + 1 x M20 arrangement • "Index of Protection" : IP56
Power supply:	• 190 ... 260 V AC - Built-in APS-90-480-OF switching mode power supply
Weight:	1.04 kg
Dimensions:	248 x 198 x 96 mm
Manufacturer / Brand:	ATTE
Guarantee:	**3 years**

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60