

Code: BCS-V-NVR1602-4K

NVR **BCS-V-NVR1602-4K** 16 CHANNELS BCS View

The BCS-V-NVR1602-4K digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



| | |
|----------------------------------|---|
| Standard: | TCP/IP |
| Supported resolutions: | max. 12 Mpx - 4000 x 3000 px |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output |
| Audio support: | 16 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 |
| Supported hard drives: | 2 x 8 TB SATA |
| Recording modes: | Manual, Motion Detection, Schedule |
| Network protocols: | TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, PPPoE, NFS, iSCSI, UPnP, HTTPS, P2P, ONVIF |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Default IP address: | DHCP or 192.168.1.64 |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) |
| Mobile client access ports: | 8000 |
| RTSP URL: | <ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream |



DATA SHEET

| | |
|-------------------------------------|--|
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow |
| Bitrate: | max. 160 Mbps |
| Intelligent Image Analysis: | crossing the line (tripwire), intrusion |
| Network functions: | Live image view, Playback the records, Backup the records |
| ONVIF: | ✓ |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application BCS View• iOS (iPhone): Free application BCS View |
| Alarm inputs / outputs: | 4 / 1 |
| PTZ control: | IP Speed Dome Cameras |
| USB: | 1 pcs USB 2.0 1 pcs USB 3.0 |
| Motion Detection: | ✓ |
| Mouse support: | ✓ |
| IR remote controller in the set: | ✓ |
| Operation temp: | -10 °C ... 55 °C |
| Power supply: | 12 V DC / 3.33 A (power adapter included) |
| Weight: | 1.76 kg |
| Dimensions: | 380 x 315 x 52 mm |
| Supported languages: | Polish, English |
| Manufacturer / Brand: | BCS View |
| Guarantee: | 3 years |