

Code: TRISET-PLUS/500

COAXIAL CABLE **TRISET-PLUS/500** Dca LSZH A+

The TRISET-PLUS/500 high-quality coaxial cable dedicated to both individual and collective installations. Cable made in LSZH (LS0H) - halogen-free insulation, used where greater safety in the event of fire is required (high-rise residential buildings, public utility buildings).



In section:	500 m . Price for 1m when buying a whole roll
Coaxial cable:	TRISET
Inner conductor:	Ø 1.13 mm Cu Wire
Dielectric:	Ø 4.8 mm (physical foam)
Shield:	• Foil : Al/PET/SY - Internal • Foil : Al/PET - External
Braid:	81 % Al wire
Outer coating:	Ø 6.85 mm PVC LSZH
Coating color:	White
Minimal bend radius:	70 mm
Impedance:	75 Ω
Capacity:	52 pF/m
Resistance of the inner conductor for DC current:	16.85 Ω/km
Dielectric resistance:	2500 MΩ/km
Screening efficiency:	> 95 dB @30 ... 1000 MHz > 85 dB @1 ... 2 GHz > 75 dB @2 ... 3 GHz
Shortening wave coefficient:	84 %
Weight:	41.4 kg/km
Main features:	• low attenuation • perfect matched • high screening efficiency • LSZH (Low Smoke Zero Halogen) coating - means small amount of toxic gases emitted during combustion
Guarantee:	2 years