

Code: TRISET-B2CA/500

COAXIAL CABLE **TRISET-B2CA/500** A++

High quality coaxial cable used in individual and MATV/SMATV/CATV antenna installations, especially recommended for cable TV (CATV) networks and for SMATV systems based on multiswitches. For convenience, cable is marking with length counter printed with 1 m distance step.

The cable complies with the EN50117 standard and A++ class requirements in the whole transmission frequency range.



In section:	500 m . Price for 1m when buying a whole roll
Coaxial cable:	TRISET
Inner conductor:	Ø 1.05 mm Cu Wire
Dielectric:	Ø 4.6 mm (physical foam)
Shield:	Triple <ul style="list-style-type: none"> • Foil - Al/PET/SY • Foil - Al/PET Screening efficiency class A++
Braid:	82 % - Cu + Sn wire
Outer coating:	Ø 6.9 mm PVC LSZH
Coating color:	White
Minimal bend radius:	35 mm
Impedance:	75 Ω
Capacity:	52 pF/m
Resistance of the inner conductor for DC current:	20 Ω/km
Screening efficiency:	> 105 dB @30 ... 1000 MHz > 95 dB @1 ... 2 GHz > 85 dB @2 ... 3 GHz
Shortening wave coefficient:	85 %
Weight:	54 kg/km
Main features:	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • The cable complies with the EN50117 standard and A++ class requirements in the whole transmission frequency range • Reaction to fire class in accordance with CPR - B2ca-s1a, d1, a1
Guarantee:	2 years