# DATA SHEET

Code: DS-2CD2346G2-ISU/SL(2.8MM)

## IP CAMERA **DS-2CD2346G2-ISU/SL(2.8MM)** ACUSENSE - 5 Mpx Hikvision

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions. Camera is according to IP67 Index of Protection norm.



| | |
|---|---|
| Standard: | TCP/IP |
| Sensor: | 1/3 " Progressive Scan CMOS |
| Matrix size: | 5 Mpx |
| Scanning system: | Progressive |
| Resolution: | 2592 x 1944 - 5 Mpx ,<br>2688 x 1520 - 4 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 720 - 720p |
| Lens: | 2.8 mm |
| View angle: | • 103 ° (manufacturer data)<br>• 94 ° (our tests result) |
| Range of IR illumination: | 30 m |
| RS-485 interface: | – |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

# DATA SHEET

| | |
|---|---|
| Alarm inputs / outputs: | 1 / 1 |
| Audio: | • 1 Input<br>• 1 Output<br>• Microphone built-in<br>• Speaker built-in, Alarm siren<br>• Bi-directional audio streaming support |
| Main stream frame rate: | 20 fps @ 5 Mpx<br>25 fps @ 4 Mpx |
| Network interface: | 10/100 Base-T (RJ-45) |
| Network protocols: | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, ARP |
| WEB Server: | Built-in |
| Max. number of on-line users: | 6 |
| ONVIF: | 18.12 |
| Main features: | • Camera from AcuSense series<br>• WDR - 120 dB - Wide Dynamic Range<br>• 3D-DNR - Digital Noise Reduction<br>• BLC/HLC - Back Light / High Light Compensation<br>• ROI - improve the quality of selected parts of image<br>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect<br>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its<br>• Day/night mode<br>• ICR - Movable InfraRed filter<br>• WB - White Balance<br>• AGC - Automatic Gain Control<br>• Possibility to change the resolution, quality and bit rate<br>• Sharpness - sharper image outlines<br>• Mirror - Mirror image<br>• Configurable Privacy Zones<br>• Motion Detection<br>• Filtering of false alarms based on the recognition of persons and vehicles<br>• Light and sound alarm,<br>• Intelligent Image Analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, scene changing, face detection, advanced face capture features |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P)<br>• Android: Free application iVMS-4500 or Hik-Connect<br>• iOS (iPhone): Free application iVMS-4500 or Hik-Connect |
| Default IP address: | 192.168.1.64 |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports: | 8000 |
| Port ONVIF: | 80 |
| RTSP URL: | • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization<br>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

# DATA SHEET

| | |
|---|---|
| Power supply: | • PoE (802.3af),<br>• 12 V DC / 650 mA |
| Power consumption: | ≤ 7.8 W @ PoE (802.3af)<br>≤ 8.8 W @ 12 V DC |
| Housing: | Dome, Metal |
| Color: | White |
| "Index of Protection": | IP67 |
| Vandal-proof: | – |
| Operation temp: | -30 °C ... 60 °C |
| Weight: | 0.82 kg |
| Dimensions: | Ø 138  x 125 mm |
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 311312481 |
| Guarantee: | **3 years** |

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60