

## DATA SHEET

## Code: DS-PDD12P-EG2-WE WIRELESS DUAL TECHNOLOGY MICROWAVE + PIR DETECTOR AX PRO **DS-PDD12P-EG2-WE** Hikvision



Wireless motion detector, which is designed to detect the moving intruder within the system protected area. With a combination of PIR and MW detection was reached high immunity to false alarms. Thanks to pet immunity, the DS-PDD12P-EG2-WE can provide protection even when small pets are moving around during surveillance.

Lithium battery to power the device ensures many years of work without having to replace it, so the system is as easy to get along in life as traditional wired solutions.

| Support:                                      | Wireless alarm systems HIKVISION AX PRO   |
|---|---|
| Frequency band:                               | 868 MHz                                   |
| Radio communication range (at open area):     | max. 1600 m                               |
| PIR detection range:                          | 12 m / 85.9 °                             |
| Power supply:                                 | 2 x CR123A 3 V Lithium battery (included) |
| Battery working time (in energy saving mode): | ~ 5 years                                 |
| Target speed range:                           | 0.3 2 m/s                                 |
| Recommended installation height:              | 1.8 2.4 m                                 |
| Pet immunity:                                 | ≤ 30 kg                                   |
| Protection class (Grade):                     | 2   |



DS-PDD12P-EG2-WE



## DATA SHEET

| Main features:                 | <ul> <li>Passive Infra Red (PIR) and microwave (MW)</li> <li>Digital detector</li> <li>SEC (Smart Environmental Control) - advanced digital signal processing and 3D optics</li> <li>24 GHz Microwave detection based on Doppler concept</li> <li>Advanced temperature compensation</li> <li>Tamper protection (detection of removing from mounting surface and enclosure opening)</li> <li>Bidirectional communication</li> <li>Compliance with the Tri-X protocol</li> <li>AES-128 data encryption</li> <li>Frequency hopping against jamming for reliable transmission</li> </ul> |
|--------------------------------|--|
| Color:                         | White  |
| Operation temp:                | -10 °C 55 °C   |
| Permissible relative humidity: | 10 % 90 %  |
| Weight:                        | 0.14 kg  |
| Dimensions:                    | 103 x 66 x 49 mm   |
| Manufacturer / Brand:          | Hikvision  |
| SAP Code:                      | 314300071  |
| Guarantee:                     | 2 years  |

