

Code: NVR4116-8P-4KS2/L

NVR **NVR4116-8P-4KS2/L** 16 CHANNELS, 8 PoE DAHUA



| | |
|-------------------------------------|---|
| Standard: | TCP/IP |
| Supported resolutions: | max. 8.3 Mpx, 4K UHD - 3840 x 2160 px |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA |
| Audio support: | 16 Channels - Audio from cameras |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Supported hard drives: | 1 x 10 TB SATA III |
| Recording modes: | Manual, Motion Detection, Schedule |
| Network protocols: | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, Alarm Server, IP Search, P2P, Auto Register, ONVIF |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow "Frame by Frame" playback function |
| Bitrate: | max. 80 Mbps |
| Network functions: | Full support via network, Remote records copying, Web Server built-in |
| ONVIF: | ✓ |



DATA SHEET

| | |
|----------------------------------|--|
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application DMSS• iOS (iPhone): Free application DMSS See how to configure the P2P function in Dahua recorders and how to enable the mobile application |
| Default IP address: | 192.168.1.108 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Mobile client access ports: | 37777 |
| RTSP URL: | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream |
| Alarm inputs / outputs: | — |
| PTZ control: | ✓ |
| Motion Detection: | ✓ |
| USB: | 2 pcs USB 2.0 |
| Main features: | Functions are realized in cooperation of the recorder with cameras that support these functions <ul style="list-style-type: none">• Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians,• classification of people and vehicles,• face detection,• people counting,• SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Switch PoE: | 8-port PoE Switch built-in, 25.5 W / Channel - PoE (802.3af/at), max. 72 W (total) |
| Power supply: | 53 V DC / 1.8 A (power adapter included) |
| Weight: | 0.7 kg |
| Dimensions: | 270 x 207 x 48 mm |
| Supported languages: | English, Polish |
| Country of origin: | China |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |