

Code: PFS3106-4ET-60-V2

INDUSTRIAL POE SWITCH **PFS3106-4ET-60-V2** 4-PORT SFP DAHUA

The PFS3106-4ET-60-V2 switch is designed for large streams of video data in the CCTV IP surveillance networks. Devices of this type can be used in installations realized in industrial facilities in harsh environmental conditions like high or low temperature.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> • 1 x port SFP 100/1000 Base-X - Uplink, • 1 x RJ45 10/100/1000 Base-T - Uplink, • 3 x RJ45 10/100 Base-T + PoE (802.3af/at), • 1 x RJ45 10/100 Base-T + Hi-PoE / PoE (802.3af/at)
Management via WWW / console:	—
LED diodes:	Power, Link/Act
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 Mbps - 4 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 1 Port LAN, • 100 / 1000 Mbps - port SFP
Maximal output power:	<ul style="list-style-type: none"> • 30 W / port PoE @ PoE (802.3af/at), • 60 W @ High PoE
Maximal total power:	60 W
MAC addresses table:	8k
Operation modes:	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps • Extend Off : 100 m, 100 Mbps



DATA SHEET

Main features:	<ul style="list-style-type: none">• Industrial wide temperature design.• PoE power mode : The device supports 8-pin power supply• Intelligent management of Power Supply Unit power's output stage• protection against lightning discharges and voltage differences and strokes between devices• Watchdog PoE / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected• The ability to connect two power adapters - redundant power supply
Certificates:	CE, FCC
Power supply:	53 V DC / 1.22 A (power adapter included)
Operation temp:	-30 °C ... 65 °C
Assembly:	DIN rail (TS-35)
Weight:	0.44 kg
Dimensions:	150 x 110 x 30 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years