

Code: VTO2202F-P-S2

VIDEO DOORPHONE **VTO2202F-P-S2** DAHUA



Attention! When selecting 2-wire devices, check the compatibility list available at the bottom of the page in the "files" section.

It is a hybrid module - it can work in a 2-Wire installation or as a standard IP video doorphone.

| | |
|----------------------------|---|
| Sensor: | 2 Mpx CMOS |
| Lens: | 1.95 mm |
| View angle: | 168 ° |
| proximity reader built-in: | — |
| Image compression method: | H.265 |
| LED illuminator: | — |
| IR illuminator: | ✓ |
| Compatibility: | DAHUA |
| RS-485: | ✓ |
| Mobile phones support: | Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS |



| | |
|------------------------|---|
| Main features: | <ul style="list-style-type: none"> • SD memory cards up to 32GB support (possible local recording), • Doorbell button, • LED diodes, • Monitoring the status of individual doors, • WDR - 120 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Power output 12 V DC / 100 mA |
| Power supply: | <ul style="list-style-type: none"> • PoE (802.3af), • 2-Wire IP interface |
| Power consumption: | ≤ 12 W |
| Housing: | Aluminum |
| Color: | Silver |
| "Index of Protection": | IP65 - after additional sealing the housing connection with the mounting surface, e.g. with silicone |
| IK rating: | IK07 |
| Operation temp: | -30 °C ... 60 °C |
| Weight: | 0.33 kg |
| Dimensions: | 130 x 96 x 28.5 mm |
| Supported languages: | Polish, English |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |