

## DATA SHEET

## Code: A30T USB VIDEO CONFERENCE CAMERA **A30T** - 1080p UNIARCH



The A30T conference camera is a combination of a camera, microphones array and a loudspeaker into one device. The A30T camera with a resolution of 2.1 Mpx and wide view angle is ideal for conducting video conferences in small-to-medium-sized teams. The built-in 4-element omni-directional microphones array, customized, human-voice-optimized wide-band speaker, enable full-duplex two-way communication within 5 meters distance with the real feeling of stable sound.

The device is equipped with a USB 2.0 connector and works according to the Plug and Play standard. The device is compatible with IoT (Internet of Things) technology. This ensures compatibility with leading online conferencing platforms. It is an excellent choice for conference rooms hosting 1 to 8 people.

Standard:	USB 2.0 / UVC
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	F2.4
View angle:	100 °
Interface:	USB 2.0
Memory card slot:	-
Image compression method:	MJPEG / H.264
Alarm inputs / outputs:	-
Audio:	<ul> <li>4 x Microphone built-in, omni-directional</li> <li>Noise and echo reduction</li> <li>Effective range of voice reception - 5 m</li> <li>AGC</li> </ul>
Main stream frame rate:	30 fps @ 1080p
Network protocols:	UVC 1.1 / 1.5



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



## DATA SHEET

Main features:	<ul> <li>Easy installation - Plug&amp;Play USB device type</li> <li>Auto White Balance</li> <li>3D-DNR - Digital Noise Reduction</li> <li>Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>AES - Auto Electronic Shutter</li> <li>WDR - Wide Dynamic Range</li> <li>Lens distortion correction</li> <li>Self-adaptive skin toning</li> <li>Bidirectional communication</li> <li>Speaker person detection</li> <li>Speaker built-in 3 W, Bandwidth 200 Hz 20 kHz</li> <li>Compatible with Windows, Linux, Mac-OS</li> </ul>
Power supply:	5 V DC / 500 mA (max) - USB-C
Housing:	Compact - Plastic
Color:	White
Length of the cable:	1.5 m
Weight:	0.62 kg
Dimensions:	Ø 110 x 270 mm
Manufacturer / Brand:	UNIVIEW / UNIARCH
Guarantee:	2 years

