

Code: APTI-AI503C2-28WP

IP CAMERA **APTI-AI503C2-28WP** - 5 Mpx 2.8 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx.

Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

The camera has extensive functions of intelligent image analysis.



Standard:	TCP/IP
Matrix size:	5 Mpx
Sensor:	1/2.7 " Progressive Scan CMOS
Resolution:	2880 x 1620 - 5 Mpx , 2592 x 1536 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"> • 95 ° (manufacturer data) • 106 ° (our tests result)
Range of IR illumination:	25 m
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Main stream frame rate:	25 fps @ 5 Mpx
Network interface:	10/100 Base-T (RJ-45)
Memory card slot:	—
Alarm inputs / outputs:	—



DATA SHEET

Audio:	—
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, UDP
WEB Server:	Built-in
Max. number of on-line users:	10
ONVIF:	2.4
RS-485 interface:	—
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application BitVision• iOS (iPhone): Free application BitVision
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none">• rtsp://user:password@ip_address:80/0 - Main stream• rtsp://user:password@ip_address:80/1 - Sub stream
Main features:	<ul style="list-style-type: none">• Intelligent Image Analysis : intrusion, face detection, detection of people gathering, motion detection based on human detection• WDR - 120 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• F-DNR (Defog) - Reduction of image noise caused by precipitation• Flicker Control - The technology eliminates the tiring eyes flickering image effect• BLC/HLC - Back Light / High Light Compensation• Possibility to change the resolution, quality and bit rate• ICR - Movable InfraRed filter• Privacy zones - max. 3• Day/Night mode - configurable• Mirror - Mirror image• Sharpness - sharper image outlines
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 330 mA
Power consumption:	≤ 4 W
Housing:	Compact - Aluminum
Color:	White
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.42 kg
Dimensions:	170 x 73 x 73 mm
Supported languages:	Polish, English, Bulgarian Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian



DATA SHEET

Manufacturer / Brand:	APTI
Guarantee:	2 years

