

Code: ASI1212F

ACCESS CONTROLLER **ASI1212F** DAHUA

The ASI1212F controller can operate autonomously or in the network mode. The device enables single door or read in/out access control. In case of read in/out access control the controller must be connected to the external access reader of the ASR series or to the reader equipped with the Wiegand interface.



Cards support:	MIFARE 13.56 MHz
Reading distance of prox-keys:	1 ... 3 cm
Keyboard built-in:	—
Autonomous operation:	✓
Battery backup support:	—
Input lines:	3
Output lines:	3
Identification time:	< 1.5 s
Communication:	<ul style="list-style-type: none"> • RS-485 • Wiegand • LAN
RS-485 interface:	✓
RS-232 interface:	—
Wiegand interface:	✓
Network interface:	10/100 Base-T
Default IP address:	192.168.1.108



DATA SHEET

Default admin user / password:	admin / - The administrator password should be set at the first start
USB:	—
Memory card slot:	—
Internal memory:	Support storage of 150 000 records
Power supply:	12 V DC / 1 A
Main features:	<ul style="list-style-type: none">• Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen• Fingerprint reader built-in• Memory of 3000 fingerprint patterns• Possible connection of the external ASR series reader (read in/out access control)• Identification modes : Proximity identifier Mifare, Fingerprint, PIN, Any combination of the above• Remote access verification• Tamper detection - removing from mounting surface• Support for door contact and exit button• Indication of forced entry and the lack of closing doors• 30000 indexed users• Possibility to configure access groups• 128 General Purpose Schedules• 128 time periods within single Schedule• Holiday Schedules• Anti-passback• Integration with an alarm system via in/out line• Remote programming from PC
"Index of Protection":	—
Operation temp:	-10 °C ... 45 °C
Permissible relative humidity:	5 ... 90 % (non-condensing)
Dimensions:	115 x 115 x 32 mm
Weight:	0.22 kg
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years