

Code: TL-SG3210

SWITCH **TL-SG3210** 8-PORT SFP TP-LINK

Due to reliability and ensuring high quality of transmission, the TL-SG3210 10/100/1000M 8-port desktop type switch is perfect solution for expanding home or office network.

The device is equipped with 2 independent Uplink ports: SFP (fiber optic). Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	Switch is managed via a web browser, command line interface and SNMP, RMON protocols <ul style="list-style-type: none"> • 8 x RJ45, • 2 x port SFP - Uplink, • 1 x RJ45 - Console
Management via WWW / console:	✓
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 8 LAN ports, • 100 / 1000 Mbps - 2 SFP ports
Jumbo Frame:	9216 B
MAC addresses table:	8k



<p>Main features:</p>	<ul style="list-style-type: none"> • Omada Central Management System • CoS/DSCP priority based on IEEE 802.1p standard • Queue scheduling: SP, WRR, SP+WRR • Port/flow-based rate limiting • IEEE 802.1Q VLAN, Port Based VLAN, MAC Based VLAN, Private VLAN support • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • GVRP (GARP VLAN Registration Protocol) support • IGMP Snooping V1/V2/V3 • Spanning Tree STP/RSTP/MSTP • BPDU Filtering/Guard • TC / Root Protect • Loop back detection • Data Flow Control (802.3x) • Storm Control function • Static routing • Static link aggregation • Port mirroring function • DHCP snooping support • Multicast • Hardware supports IP + MAC binding based on port • Access Control List - L2/L4 ACL package filtering based on source and destination MAC addresses • IEEE 802.1x and Radius Authentication • Support DoS defence • Port Security • IPv6 compliance • SSL, SSH • Console : RJ-45 output, micro USB • Can be mounted in a Rack 19" cabinet
LED diodes:	Power, Link/Act, System, Speed
Certificates:	CE
Power supply:	100 ... 240 V AC
Weight:	1.21 kg
Dimensions:	294 x 180 x 44 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years