

Code: BCS-L-SNVR0401-4KE

## IP DVR **BCS-L-SNVR0401-4KE** 4 CHANNELS



|                                     |  |
|-------------------------------------|--|
| Standard:                           | TCP/IP   |
| Supported resolutions:              | max. 8.3 Mpx - 3840 x 2160 px  |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA   |
| Audio support:                      | 4 Channels - Audio from cameras  |
| Audio inputs:                       | 1 pcs CINCH  |
| Audio outputs:                      | 1 pcs CINCH  |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264 / MJPEG  |
| Supported hard drives:              | 1 x 10 TB SATA   |
| Recording modes:                    | Manual, Motion Detection, Schedule   |
| Network protocols:                  | HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, Alarm Server, IP Search, P2P, ONVIF   |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)   |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>All channels synchronous playback, Smart Search function |
| Bitrate:                            | max. 80 Mbps   |
| Network functions:                  | Full support via network, Remote records copying, Web Server built-in  |
| Default admin user / password:      | admin / admin  |
| Default IP address:                 | 192.168.1.108  |
| Web browser access ports:           | 80, 37777  |

|                                  |  |
|----------------------------------|--|
| PC client access ports:          | 37777  |
| Mobile client access ports:      | 37777  |
| RTSP URL:                        | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream  |
| ONVIF:                           | ✓  |
| Mobile phones support:           | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">DMSS</a><br>• iOS (iPhone): Free application <a href="#">DMSS</a>  |
| Alarm inputs / outputs:          | —  |
| PTZ control:                     | IP Speed Dome Cameras  |
| Intelligent Image Analysis:      | ✓  |
| Motion Detection:                | ✓  |
| Main features:                   | <ul style="list-style-type: none"> <li>• CMS application</li> <li>• Motion Detection</li> <li>• Privacy zones</li> </ul> <p>Functions are realized in cooperation of the recorder with cameras that support these functions</p> <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> <li>• face detection</li> <li>• SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor vehicle</li> </ul> |
| Mouse support:                   | ✓  |
| IR remote controller in the set: | —  |
| Power supply:                    | 12 V DC / 2 A (power adapter included)   |
| Weight:                          | 0.45 kg  |
| Dimensions:                      | 206 x 205 x 48 mm  |
| Supported languages:             | English, Polish  |
| Country of origin:               | China  |
| Manufacturer / Brand:            | BCS  |
| Guarantee:                       | <b>3 years</b>   |