

DATA SHEET

Code: KTA02

VIDEO DOORPHONE KIT **KTA02** DAHUA







DOOR STATION:	
Sensor:	1.3 Mpx CMOS
Camera view angle:	70 °
IR illuminator:	Built-in Infra-Red illuminator enables night monitoring
proximity reader built-in:	-
Video output:	compatible with DAHUA analog video door-phone system
Audio inputs:	1 - Microphone
Audio outputs:	1 - Speaker
Main features:	D-WDR - Wide Dynamic Range ICR - Movable InfraRed filter Operation status LED indicator - green LED - power indicator Doorbell button Inputs : Exit button, Door status detection Surface mount Rain cover included
Power supply:	12 V DC / 1 A (powered by indoor monitor)
Power consumption:	≤ 3 W Operation ≤ 1 W Standby
Housing:	Plastic (PC + ABS)
Color:	Silver + Black



DATA SHEET

"Index of Protection":	IP66 - after additional sealing the housing connection with the mounting surface, e.g. with silicone	
Operation temp:	-30 °C 60 °C	
Weight:	0.14 kg	
Dimensions:	46 x 131 x 34 mm	
INDOOR PANEL:		
Shield:	7 " TFT-LCD color matrix	
Resolution:	1024 x 600	
Main features:	Touch control keys, Operation status LED indicator - green LED - power indicator, The maximum number of gate stations in the system : 2, The maximum number of indoor panels in the system : 3, Selecting the ringer melody, Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, Preview image from the door station with the possibility of turning on the sound and opening the gate, 4-wire cable installation, Communication: compatible with DAHUA analog video door-phone system Surface mount, In the kit: Bracket	
Power supply:	12 V DC / 1 A - Monitor 12 V DC / 2 A (power adapter included)	
Power consumption:	≤ 5 W Operation ≤ 2 W Standby	
Housing:	Plastic (PC + ABS)	
Color:	White	
Operation temp:	-10 °C 55 °C	
Weight:	0.25 kg	
Dimensions:	183 x 134 x 18 mm	
Manufacturer / Brand:	DAHUA	
Guarantee:	3 years	