

Code: ATLO-KRM-203

CODE LOCK **ATLO-KRM-203**

Indoor, autonomous code lock with RFID reader.

Autonomous operation of the device allows the user to:

- Open by using a card or PIN code.
- Remember stored cards or PIN codes.
- Signaling left the door open.
- Acoustic and optical signaling.

Administrator capabilities are following:

- Programming by using the keypad.
- Adding a new card by using the keypad.

Attention! No backlit keyboard.



Cards support:	13.56 MHz S50
Reading distance of prox-keys:	1 ... 3 cm
Autonomous operation:	✓
Keyboard built-in:	✓
Communication:	Wiegand 26, Wiegand 34
Doorbell button:	✓
Tamper output:	—
Power supply:	12 V DC ± 10%
Maximal current consumption:	≤ 30 mA (Standby mode) ≤ 60 mA (operation)
Relay contacts load:	3 A / 12 V



DATA SHEET

Main features:	<ul style="list-style-type: none">• Number of relay outputs : 1,• 2000 indexed users,• Wiegand interface 26 / 34 bit• Identification: Card and/or PIN• Support for door contact and exit button• Electric strikes and electromagnetic locks support• Reversing bolt support• NO/NC output
Operation temp:	-40 °C ... 60 °C
Permissible relative humidity:	10 ... 90 % (non-condensing)
"Index of Protection":	IP40
Housing:	Self-extinguishing ABS
Color:	Black + Silver
Vandal-proof:	—
Weight:	0.08 kg
Dimensions:	75 x 115 x 18 mm
Manufacturer / Brand:	ATLO
Guarantee:	3 years