

Code: WS-6944P

UNIVERSAL METER **WS-6944P** DVB-T/T2 DVB-S/S2 DVB-C

The WS-6944P allows to measure the TV signals at DVB-T/T2, DVB-S/S2, DVB-C/C2 installations. Readable menu will help the operation for any installer.

Attention! The built-in compass is too inaccurate to correctly determine the direction.



Output and input:	1 pcs F socket, 1 pcs IEC socket, 1 pcs micro USB
Display:	2.4 " TFT LCD
Frequency range:	<ul style="list-style-type: none"> • 42 MHz ... 862 MHz - DVB-T / DVB-T2 / DVB-C / DVB-C2, • 950 MHz ... 2150 MHz - DVB-S / DVB-S2
Signal level:	-65 ... -25 dBm
LNB power supply:	13/18 V
Switching between bandwidths:	22 kHz
DiSEqC:	1.0, 1.1, 1.2, 2.0
Programming and firmware upgrade:	via USB port
Battery power supply:	Li-Poly battery : 7.4 V / 2500 mAh Power adapter 12 V / 1 A (power adapter included)
Main features:	<ul style="list-style-type: none"> • Sound signaling • DiSEqC and 22kHz control support • Flashlight built-in
Weight:	0.3 kg
Dimensions:	165 x 94 x 40 mm



DATA SHEET

Supported languages:	Polish, English, Spanish, Portuguese, Russian
Guarantee:	2 years

