

Code: ALINK-M960

MODEM 4G LTE, MOBILE ROUTER **ALINK-M960** Wi-Fi 150Mb/s

Portable LTE hotspot. The device does not require any additional configuration, it is ready to use immediately after placing the SIM card inside and connecting the power supply.

The ALINK-M960 supports the latest generation of 4G FDD/TDD-LTE connections, ensuring a seamless connection to the Internet in most countries and regions. The device allows you to easily share the network connection up to 10 devices simultaneously.



Frequency range:	2.4 GHz
Antenna type:	1 x WiFi - Internal antenna , 1 x 4G LTE - Internal antenna
Standards:	IEEE 802.11 b/g/n, 4G LTE, 3G DC-HSPA+/HSPA/UMTS
Baud rates:	<ul style="list-style-type: none"> • LTE : 150 / 50 Mbps, • 11n : 300 Mbps, • 11g : 54 Mbps, • 11b : 11 Mbps
Network type:	<ul style="list-style-type: none"> • 4G : FDD-LTE B1/B3/B7/B8/B20 - 2100 / 1800 / 2600 / 900 / 800 MHz • 4G : TDD-LTE B38/B40 - 2600 / 2300 MHz • 3G : DC-HSPA+/HSPA/UMTS B1/B8 - 2100 / 900 MHz
LAN ports:	—
Ports:	<ul style="list-style-type: none"> • 1 x micro USB - Battery charging • 1 x SIM socket
Receiver sensitivity:	<ul style="list-style-type: none"> • 11b 11 Mbps : -87.5 dBm • 11g 54 Mbps : -74 dBm • 11n HT20 MCS7 : -70 dBm • 11n HT40 MCS7 : -68 dBm
Transmitter power:	< 20 dBm

Main features:	<ul style="list-style-type: none">• ON/OFF button• RESET button• LED diodes : GSM, Battery• Transmission encryption : WPA-PSK/WPA2-PSK• MAC addresses filtering• SSID hiding• DHCP server• DHCP client list• Max. number of supported devices : 10• Backup time max. 6 h• Remote management - Web browser• Default address : 192.168.100.1• System requirements : Windows XP/Vista/7/8/10, Mac OS, Android, iOS (iPhone, iPad)
Power supply:	<ul style="list-style-type: none">• 1800 mAh Battery• 5 V DC / 1 A Charging via micro USB port
Operation temp:	0 °C ... 35 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.042 kg
Dimensions:	98 x 59 x 13 mm
Manufacturer / Brand:	ALINK
Guarantee:	2 years