

Code: ARCHER-C64

ROUTER **ARCHER-C64** 2.4 GHz, 5 GHz 400 Mbps + 867 Mbps TP-LINK

With 867 Mbps wireless speeds over the crystal clear 5 GHz band and 400 Mbps over the 2.4 GHz band, ARCHER-C64 offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. 4 external antennas provide stable omnidirectional signal and superior wireless coverage.

Supports 802.11ac standard - the next generation of Wi-Fi.



Frequency range:	2.4 GHz, 5 GHz
Antenna type:	4 x Omnidirectional antenna - Integrated
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Baud rates:	400 Mbps + 867 Mbps
LAN ports:	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink
LED indicators:	Power, 2.4 GHz WLAN, 5 GHz WLAN, Ethernet, WAN
Receiver sensitivity:	2.4 GHz : • 11g 6M : -96 dBm • 11g 54M : -78 dBm • 11n HT20 MCS7 : -77 dBm • 11n HT40 MCS7 : -74 dBm • 11ac VHT20 MCS8 : -73 dBm • 11ac VHT40 MCS9 : -68 dBm 5 GHz : • 11a 6M : -95 dBm • 11a 54M : -77 dBm • 11ac VHT20 MCS8 : -71 dBm • 11ac VHT40 MCS9 : -67 dBm • 11ac VHT80 MCS9 : -63 dBm





DATA SHEET

DDNS:	✓
DHCP server:	✓
Firmware update:	✓
Protections:	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface:	Web browser, TP-LINK Tether
Transmitter power:	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz
Power supply:	12 V DC / 1.5 A (power adapter included)
Main features:	<ul style="list-style-type: none">• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source• Airtime Fairness - technology that improves network performance when multiple clients with different data rates appear in it• Firewall• Internet access filtering• Static / dynamic routing• Built-in 4-port switch• Access Point• The WPS function allows to easy establish an encrypted connection• QoS• Access control• Remote management• DMZ• UPnP• Port forwarding• parental control• Guest Network - a separate and secure network for guests• DHCP client list• VPN networks: Open VPN, PPTP VPN• SSID hiding• IPv6 compliance• Smooth transmission in HD quality - IGMP Proxy/Snooping, Bridge VLAN, Tag VLAN functions contribute to optimal IPTV transmission
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.23 kg
Dimensions:	120 x 120 x 28 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years