

Code: MCT82M-IO

## PROXIMITY READER WITH KEYPAD **MCT82M-IO** ROGER

Indoor proximity cards and key-fobs reader. MIFARE 13.56 MHz standard.

The readers with IO option offer the set of inputs and outputs which, in most cases, should be capable to operate single door passage without necessity to use inputs or outputs located on access controller or expansion unit.



Support:	RACS 5 (Roger)
Cards support:	MIFARE 13.56 MHz
Reading distance of prox-keys:	max. 7 cm
Keyboard built-in:	✓
Autonomous operation:	✓
Doorbell button:	—
Tamper output:	✓
Communication:	RS-485
Main features:	<ul style="list-style-type: none"> <li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li> <li>• LED indication</li> <li>• Beep signal</li> <li>• Touch and backlit keyboard buttons</li> <li>• 3 Inputs,</li> <li>• Multifunctional parametric inputs including Double Wiring</li> <li>• 2 Transistor outputs,</li> <li>• 1 Relay output</li> </ul>
Power supply:	10 ... 15 V DC



# DATA SHEET

Average current consumption:	60 mA
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	10 ... 95 % (non-condensing)
"Index of Protection":	IP41
Weight:	0.12 kg
Dimensions:	85 x 85 x 22 mm
Manufacturer / Brand:	ROGER
Guarantee:	<b>3 years</b>