

Code: MC440

## SIDE MAGNETIC CONTACT **MC440** ALARMTECH

The magnetic contacts can be used wherever required for controlling the status of doors, windows and/or other movable elements, e.g. for protection or monitoring of access to particular sites, spaces, facilities, in automatic control systems, etc.

The contact is designed for surface mounting.



Detection:	Opening the door or window
Maximum reed switched voltage:	48 V
Maximum switched current:	500 mA
Make distance:	37 mm Wood / 24 mm Steel
Break distance:	40 mm Wood / 25 mm Steel
Tamper output:	✓
Main features:	<ul style="list-style-type: none"> <li>• Plastic (ABS)</li> <li>• NC output - a magnet close to a reed switch - does not trigger an alarm, the contacts are closed</li> <li>• Connectors : screw terminals</li> <li>• Compliance to EN 50131-2-6 @ Grade 2 standard</li> <li>• Environmental class EN 50130-5 : Class II</li> <li>• "Index of Protection" : IP43</li> </ul>
Color:	White
Operation temp:	-40 °C ... 70 °C
Weight:	0.04 kg
Dimensions:	65 x 20.6 x 14.8 mm - Reed switch 65 x 14.5 x 14.8 mm - magnet
Manufacturer / Brand:	ALARMTECH
Guarantee:	2 years