

Code: ASA3213GL-MW

TIME & ATTENDANCE RECORDER **ASA3213GL-MW** DAHUA

Access controller with face recognition function.



| | |
|--------------|---------------------|
| Sensor: | CMOS |
| Matrix size: | 2 Mpx |
| Resolution: | 1920 x 1080 - 1080p |

General information:

| | |
|--------------------------------------|--|
| Standard: | TCP/IP |
| IR illuminator: | ✓ |
| LED illuminator: | ✓ |
| Temperature measurement: | — |
| Temperature measurement range: | — |
| Accuracy of temperature measurement: | — |
| Face recognition distance: | 0.3 m ... 1.5 m (max 500 faces in the database) |
| RFID proximity reader built-in: | <ul style="list-style-type: none"> • MIFARE 13.56 MHz • Memory of 500 RFID cards |
| Internal memory: | Support storage of 150 000 records |



| | |
|--------------------------------|--|
| Video output: | — |
| RS-485 interface: | ✓ |
| RS-232 interface: | — |
| Wiegand interface: | — |
| USB: | 1 x USB 2.0 |
| Memory card slot: | — |
| Alarm inputs / outputs: | 1 / 1 - Relay outputs |
| Audio: | Voice message |
| Network interface: | 1 x 10/100 Base-T (RJ-45) |
| Network protocols: | IPv4, RTSP, RTP, TCP, UDP, P2P |
| WEB Server: | Built-in |
| ONVIF: | — |
| Default IP address: | 192.168.1.108 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 37777 |
| PC client access ports: | 37777 |
| Main features: | <ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier Mifare, Face recognition, Any combination of the above • 500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Recording of information about Time&Attendance • The possibility of programming group or individual work schedules, taking into account the permissible time of lateness and earlier exit • Statistical Reporting • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Tamper protections |
| Power supply: | 12 V DC / 1.5 A (power adapter included) |
| Power consumption: | ≤ 18 W |
| Housing: | Plastic (ABS) |
| Color: | Black + Silver |
| "Index of Protection": | — |
| Operation temp: | -10 °C ... 55 °C |
| Weight: | <ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand) |



DATA SHEET

| | |
|-----------------------|--|
| Dimensions: | <ul style="list-style-type: none">• 116 x 107 x 22 mm (without stand)• 116 x 107 x 78 mm (with stand) |
| Supported languages: | English |
| Manufacturer / Brand: | DAHUA |
| Guarantee: | 3 years |

