

Code: ASI3213G-MW

ACCESS CONTROLLER **ASI3213G-MW** DAHUA

Access controller with face recognition function.



Sensor:	CMOS
Matrix size:	2 Mpx
Resolution:	1920 x 1080 - 1080p

General information:

Standard:	TCP/IP
IR illuminator:	✓
LED illuminator:	✓
Temperature measurement:	—
Temperature measurement range:	—
Accuracy of temperature measurement:	—
Face recognition distance:	0.3 m ... 1.5 m (max 1500 faces in the database)
RFID proximity reader built-in:	<ul style="list-style-type: none"> • 13.56 MHz S50 • Memory of 1500 RFID cards
Internal memory:	Support storage of 150 000 records





DATA SHEET

Video output:	—
RS-485 interface:	✓
RS-232 interface:	—
Wiegand interface:	—
USB:	1 x USB 2.0
Memory card slot:	—
Alarm inputs / outputs:	1 / 1 - Relay outputs
Audio:	Voice message
Network interface:	1 x 10/100 Base-T (RJ-45)
Network protocols:	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server:	Built-in
ONVIF:	—
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Main features:	<ul style="list-style-type: none">• Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px• Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above• 1500 users• Software update via network• Real-time Surveillance• Multiple Authentication• Take face image after swiping card• Auto-Registration• Backup to USB drive (pendrive, external drive)• Output button support• Door status detection• Lock control• Function to prevent of multiple use of the same code/card to gain access (anti-passback)• Auto-uploads alarm messages to Master or client station after entering the duress code to open the door• Ability to work with reed switch and signalling the door being opened too long• 128 General Purpose Schedules• Unlocking the transition only when more than one user is present• Tamper protections
Power supply:	12 V DC / 1.5 A (power adapter included)
Power consumption:	≤ 18 W
Housing:	Plastic (ABS)
Color:	Black + Silver
"Index of Protection":	—
Operation temp:	-10 °C ... 55 °C



DATA SHEET

Weight:	<ul style="list-style-type: none">• 0.22 kg (without stand)• 0.24 kg (with stand)
Dimensions:	<ul style="list-style-type: none">• 116 x 107 x 22 mm (without stand)• 116 x 107 x 78 mm (with stand)
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

