

Code: ASI1202M-D

## ACCESS CONTROLLER + RFID **ASI1202M-D** DAHUA

External, autonomous access controller with a built-in fingerprint reader and RFID reader.



Cards support:	Unique EM 125kHz
Reading distance of prox-keys:	max. 1 ... 3 cm
Autonomous operation:	✓
Keyboard built-in:	—
Doorbell button:	—
Tamper output:	✓
RS-485 interface:	✓
Communication:	Wiegand
Power supply:	12 V DC
Maximal current consumption:	250 mA
Identification time:	< 1.5 s
Network interface:	RJ-45 - 10/100 Base-T
Default IP address:	192.168.1.108
Default admin user / password:	admin / -

Main features:	<ul style="list-style-type: none"><li>• Memory of 3000 fingerprint patterns</li><li>• Memory of 30000 RFID cards</li><li>• Full support via network</li><li>• Function of protection against multiple use of the same card for access (anti-passback)</li><li>• Door contact and request button for exit inputs</li><li>• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value</li><li>• Port USB</li><li>• Blue backlight</li></ul>
Operation temp:	-30 °C ... 50 °C
Permissible relative humidity:	5 ... 95 % (non-condensing)
Housing:	Vandal-proof, IK10, Metal + Tempered glass
"Index of Protection":	IP65
Color:	Black + Silver
Weight:	0.71 kg
Dimensions:	159 x 55 x 35 mm
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>