
DATA SHEET

Code: HPSB-12V7A-C

BUFFERED SWITCHING POWER SUPPLY ADAPTER **HPSB-12V7A-C** PULSAR

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment.

Please pay attention for proper cooling conditions of the power adaptor during work!



Adapter type:	Switching
Input voltage:	200 V ... 240 V AC
Output voltage:	11.0 V ... 13.8 V (buffer operation)
Max. output current (total):	7 A
Battery charging current:	1 A / 2 A
Power:	97 W
Number of outputs:	1
Protections:	• Short-circuit • Overload • Overvoltage • Tamper • Reverse polarity connection • Discharge
Adapter operation control:	• AC input voltage presence indication AC • DC output voltage presence indication DC • Battery charging
Place for battery:	12V/17Ah
Max. battery dimensions:	250 x 172 x 100 mm
Weight:	2.3 kg
Dimensions:	305 x 305 x 113 mm

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Manufacturer / Brand:	PULSAR
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60