

Code: UNIFI-U6-LITE

## ACCESS POINT **UNIFI-U6-LITE** UBIQUITI

The UBIQUITI UNIFI-U6-LITE is a device working in 2x2 MIMO (Multiple Input Multiple Output) standard.

The device is easy to use and manage. The distinguishing feature of the product is additional software UniFi WiFi Enterprise System, which enables configuration and management of the UniFi devices network, from computer via a web browser.



Frequency range:	2.4 GHz / 5 GHz
Antenna type:	2x2 MIMO, 2.4 GHz - 2.8 dBi / 5.0 GHz - 3 dBi, Integrated - 2 x Omnidirectional antenna
Standards:	<ul style="list-style-type: none"> <li>• IEEE 802.11a,</li> <li>• IEEE 802.11b,</li> <li>• IEEE 802.11g,</li> <li>• IEEE 802.11n,</li> <li>• IEEE 802.11ac,</li> <li>• IEEE 802.11ax</li> </ul>
Baud rates:	<ul style="list-style-type: none"> <li>• 1201 Mbps @ 5 GHz,</li> <li>• 300 Mbps @ 2.4 GHz</li> </ul>
Protections:	WEP, WPA-PSK, WPA-Enterprise (WPA/WPA2, TKIP/AES)
LAN ports:	1 x 10/100/1000 Mbps
Operating system:	UniFi WiFi Enterprise System
Transmitter power:	<ul style="list-style-type: none"> <li>• 20 dBm @ 2.4 GHz (max)</li> <li>• 20 dBm @ 5.0 GHz (max)</li> </ul>
Power supply PoE:	Ubiquiti Passive PoE
Power supply:	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 44 ... 57 V DC / 0.25 A - PoE Adapter (not included)</li> </ul>

Power consumption:	12 W
Main features:	<ul style="list-style-type: none"><li>• Possibility to mount on the wall or ceiling</li><li>• UniFi WiFi Enterprise System</li><li>• AP placement and RF maps</li><li>• Easy and uniform management system for many devices</li><li>• Intuitive installation and configuration of many advanced functions</li></ul>
Operation temp:	-30 °C ... 60 °C
Permissible relative humidity:	5 % ... 95 %
Weight:	0.33 kg
Dimensions:	Ø 160 x 31.5 mm
Manufacturer / Brand:	UBIQUITI
Guarantee:	2 years