

Code: CD-2-BR

CURTAIN PIR DETECTOR **CD-2-BR** SATEL



The curtain detector provides a narrow detection angle.

Application:	Indoor
Pyroelectric sensor:	Double
Sensor type:	Passive Infra Red (PIR)
Range:	5 x 1 m, 15 °
Sensitivity adjustment:	✓
Alarm outputs:	NC
Prealarm feature:	—
Alarm time:	2 s
Maximal outputs load:	40 mA / 24 V DC
Digital temperature compensation:	✓
Pet immunity:	—
Power supply:	12 V DC / 7 mA (max)
Operation temp:	-10 °C ... 55 °C
Target speed range:	0.3 ... 1 m/s



DATA SHEET

Main features:	<ul style="list-style-type: none">• Curtain lens• digital detection algorithm with temperature compensation for high immunity to false alarms and repeatability of parameters• Monitoring of motion detection system• Supply voltage control• Tamper detection - opening the enclosure, removing from mounting surface• LED indication• Compliance with EN 50130-4, EN 50130-5 standards• Environmental class EN 50130-5 : II
Color:	Brown
Weight:	0.022 kg
Dimensions:	105 x 25 x 20 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years