DATA SHEET

Code: MPB-300

WIRELESS PANIC BUTTON **MPB-300** SATEL



This button is a device designed to instantly trigger the alarm and (or) initiate the procedure of reporting an emergency situation in protected facility to the monitoring station. The button can also be used to control various devices (e.g. automation or access control system devices). The device has two operating modes: detector or keyfob, selected during startup.

The device is supported by: PERFECTA alarm control panels (WRL models), VERSA-MCU controller, MTX-300 controller, MICRA alarm module (firmware version 2.02 or later).

Support:	• Wireless alarm systems SATEL MICRA, • Alarm control panels PERFECTA-xx-WRL, • Wireless system control VERSA-MCU / MTX-300, • RK radio controllers
Frequency band:	433.05 ... 434.79 MHz
Radio communication range (at open area):	max. 600 m PERFECTA , max. 500 m MICRA / VERSA-MCU / MTX-300 , max. 300 m MRU-300
Main features:	• Application : Internal • Operation modes : detector or keyfob, selected during startup, • Transmission encryption • battery diagnostics • LED indication • Tamper detection - opening the enclosure, removing from mounting surface • Environmental class EN 50130-5 : II
Power supply:	1 x battery CR14250 3 V (included)
Current consumption:	• 11 mA (max) • 12 µA (Standby mode)
Battery lifetime:	~ 2 years
Operation temp:	-10 °C ... 55 °C

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

DATA SHEET

Permissible relative humidity:	93 % ± 3 %
Weight:	0.054 kg
Dimensions:	Ø 97 x 29 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60