

Code: DS-2CD2346G2-ISU/SL(2.8MM)(C)

## IP CAMERA **DS-2CD2346G2-ISU/SL(2.8MM)(C)** ACUSENSE - 4 Mpx Hikvision

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions. Camera is according to IP67 Index of Protection norm.



|                           |   |
|---------------------------|---|
| Standard:                 | TCP/IP  |
| Sensor:                   | 1/3 " Progressive Scan CMOS   |
| Matrix size:              | 4 Mpx   |
| Scanning system:          | Progressive   |
| Resolution:               | 2688 x 1520 - 4 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 720 - 720p   |
| Lens:                     | 2.8 mm  |
| View angle:               | <ul style="list-style-type: none"> <li>• 103 ° (manufacturer data)</li> <li>• 100 ° (our tests result)</li> </ul> |
| Range of IR illumination: | 30 m  |
| RS-485 interface:         | —   |
| Memory card slot:         | Micro SD memory cards up to 256GB support (possible local recording)  |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG   |
| Alarm inputs / outputs:   | 1 / 1   |



# DATA SHEET

|                                |   |
|--------------------------------|---|
| Audio:                         | <ul style="list-style-type: none"><li>• Microphone built-in</li><li>• 1 Audio input</li><li>• 1 Audio output</li><li>• Speaker built-in - Alarm siren</li><li>• Bi-directional audio streaming support</li></ul>  |
| Main stream frame rate:        | 25 fps @ 4 Mpx  |
| Network interface:             | 10/100 Base-T (RJ-45)   |
| Network protocols:             | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, ARP   |
| WEB Server:                    | Built-in  |
| Max. number of on-line users:  | 6   |
| ONVIF:                         | 18.12   |
| Main features:                 | <ul style="list-style-type: none"><li>• Camera from AcuSense series</li><li>• WDR - 120 dB - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• BLC/HLC - Back Light / High Light Compensation</li><li>• ROI - improve the quality of selected parts of image</li><li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li><li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li><li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li><li>• Day/night mode</li><li>• ICR - Movable InfraRed filter</li><li>• Auto White Balance</li><li>• AGC - Automatic Gain Control</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Sharpness - sharper image outlines</li><li>• Mirror - Mirror image</li><li>• Configurable Privacy Zones</li><li>• Motion Detection</li><li>• Filtering of false alarms based on the recognition of persons and vehicles</li><li>• Light and sound alarm,</li><li>• Intelligent Image Analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection, advanced face capture features</li></ul> |
| Mobile phones support:         | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS: Free application <a href="#">Hik-Connect</a></li></ul>   |
| Default IP address:            | 192.168.1.64  |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start  |
| Web browser access ports:      | 80  |
| PC client access ports:        | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application   |
| Mobile client access ports:    | 8000  |
| Port ONVIF:                    | 80  |



# DATA SHEET

|                        |  |
|------------------------|--|
| RTSP URL:              | <ul style="list-style-type: none"><li>• Main stream<br/>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization</li><li>• Sub stream<br/>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization</li></ul> |
| Power supply:          | <ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 650 mA</li></ul>  |
| Power consumption:     | <ul style="list-style-type: none"><li>≤ 8.8 W @ PoE (802.3af)</li><li>≤ 7.8 W @ 12 V DC</li></ul>  |
| Housing:               | Dome, Metal  |
| Color:                 | White  |
| "Index of Protection": | IP67   |
| Vandal-proof:          | —  |
| Operation temp:        | -30 °C ... 60 °C   |
| Weight:                | 0.84 kg  |
| Dimensions:            | Ø 138 x 125 mm   |
| Supported languages:   | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Vietnamese, Italian       |
| Manufacturer / Brand:  | Hikvision  |
| SAP Code:              | 311315175  |
| Guarantee:             | <b>3 years</b>   |