

Code: EXT-POE2H

EXTENDER **EXT-POE2H** IN A HERMETIC CASING PULSAR

The EXT-POE2H increases the range of Ethernet data and PoE power by another 100 meters. The output voltage is compatible with the input voltage.

The product meets the IP56 tightness class.

Attention! The device can not be used in Gigabit Ethernet networks, where all pairs of twisted-pair cable are used for data transmission.



Standards:	PoE : IEEE 802.3at, IEEE 802.3af
Input voltage:	42 ... 57 V DC
Output voltage:	42 ... 57 V DC
Number of inputs:	1
Number of outputs:	2
Connector:	3 x RJ-45 socket
LED indicators:	LAN, PoE
Supported data rates:	<ul style="list-style-type: none"> • Range : 100 m - Input, 100 m - 2 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet
Output power:	15.4 W / Port PoE OUT 1/2 , max. 20 W (total)
Protections:	<ul style="list-style-type: none"> • Overvoltage • Overload • Short-circuit
Housing:	Plastic, hermetic
"Index of Protection":	IP56
Operation temp. / Relative humidity:	-10 ... 40 °C / 10 ... 90 %



DATA SHEET

Weight:	0.55 kg
Dimensions:	198 x 148 x 78 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years