

Code: S-22

SATELLITE METER **S-22** DVB-S/S2/S2X Spacetronek

The S-22 allows to measure the TV signals at DVB-S/S2/S2X installations. Readable menu will help the operation for any installer.



Output and input:	1 pcs F socket, 1 pcs micro USB, 1 pcs 2.1/5.5 mm socket
Display:	2.4 " TFT LCD
Frequency range:	950 MHz ... 2150 MHz - DVB-S / DVB-S2 / DVB-S2X
Signal level:	-25 ... -65 dBm
LNB power supply:	13 / 18 V, 350 mA
Switching between bandwidths:	0 / 22 kHz
DiSEqC:	DiSEqC 1.0, 1.1, 1.2, USALS systems support
Antenna powering:	—
Video signal test:	—
Programming and firmware upgrade:	via micro USB port
Battery power supply:	<ul style="list-style-type: none"> • Li-Ion battery 7.4 V / 2500 mAh • 12 V / 2 A (power adapter included)



DATA SHEET

Main features:	<ul style="list-style-type: none">• Measurement of signal strength and quality• Signal indicator : LED display / Beep signal• Measurement of BER, PWR, SNR• Spectrum measurement mode• Support for a satellite dish motor• UNICABLE technology support• Support loop search function (signal preview on 8 frequencies simultaneously)• Signal lock audible notification• Clear graphical interface• OSD menu full in Polish• Built-in compass• Long standby time• Low power consumption• Compass• Flashlight built-in• Illuminated buttons• Anti-shock silicone case
Weight:	0.31 kg
Dimensions:	164 x 93 x 42 mm
Supported languages:	Polish, English, French, German, Portuguese, Russian
Manufacturer / Brand:	Spacetronik
Guarantee:	2 years

